Guardex

SF-5030A

X-RAY BAGGAGE SCANNER

Opeerting Environment :

* storge Temperature : -20°C to 60°C
* Operating Temperature : 0°C to 45°C
* Relative Humidity :20 to 95% non-condensing
* System Power : 220 VAC (+10%) 50=3HZ
* Power Wastage : 1.0 KW (Max)
* Noise < 65DB

bilmak security systems

T : 0 212. 225 80 50 pbx
M : bilmak@bilmak.com.tr
www.bilmak.com.tr

CE | RoHS COMPLIANT | ISO 9001 | FC

Guardex

SF-5030A

X-RAY BAGGAGE SCANNER

GENERAL SPECIFICATIONS :

* Tunnel Size : 500 (W) ×300(H) mm
* Conveyor Speed : 0.22m/s
* Conveyor Max Load : 100 kg
* Single inspection dosage : < 1.32uGy
* Wire Resolution : 40AWG
* Steel Penetration:10 mm
* Film Safety : For Iso 1600

X-RAY GENERATOR :

* Orientation : Upward
* Tube Current : 0.4~0.7MA (adjustable)
* Anode voltage : 80KV (adiustable)
* X-ray divergence angle:60°
* Generator cooling/Working periods :sealed oil bath with forced air/100%

X-RAY Sensor :

L-shaped array detector, 24bit

bilmak security systems

T : 0 212. 225 80 50 pbx
M : bilmak@bilmak.com.tr
www.bilmak.com.tr

CE | RoHS COMPLIANT | ISO 9001 | FC