

|                          |                              |
|--------------------------|------------------------------|
| Model NO.                | QH-1139C-2                   |
| <b>VIDEO</b>             |                              |
| Image Device             | 1/3.7" DIS                   |
| TV System                | PAL/NTSC                     |
| Effective Pixels         | 640(H)x480(V)                |
| Scanning System          | 2:1 Interlace                |
| Synchronization          | Internal                     |
| Horizontal Resolution    | 500TVL                       |
| Min. Illumination        | 0 Lux (LED on)               |
| S/N Ratio                | >52dB                        |
| Video Output             | 1Vp-p, 75ohm, BNC            |
| <b>LENS</b>              |                              |
| Focal Length             | 3.6mm or 6mm Fixed Lens, M12 |
| <b>OPERATIONAL</b>       |                              |
| Day & Night              | Auto (ICR)                   |
| Backlight Compensation   | Auto                         |
| Gain control             | Auto                         |
| White Balance            | Auto                         |
| Electronic Shutter Speed | 1/25 ~ 1/15,000sec           |
| Infrared LED             | 24 EA                        |
| IR Distance              | 10 ~ 20 Meters               |
| IR-CUT                   | NO                           |
| Infrared Spectrum        | 850nm                        |
| <b>ENVIRONMENTAL</b>     |                              |
| Operation Temperature    | -10°C ~ +50°C                |
| Storage Temperature      | -20°C ~ +60°C                |
| Water-proof Casing       | IP66                         |
| <b>ELECTRICAL</b>        |                              |
| Input Voltage/Current    | DC12V300mA                   |
| Adapter Requirement      | DC12V1A                      |
| <b>MECHANICAL</b>        |                              |
| Color                    | white                        |
| Bracket                  | All-Oriented Bracket         |
| Dimensions               | 128*90*70mm                  |
| Net Weight               | 300g/pcs                     |