

Model NO.	QH-NP6061
Operation	
OSD menu	English, Chinese, , Russian, Spanish Optional
Preset position	256 Preset Positions
Scan	Auto scan and left-right limited scan, speed adjustable
Patrol	8 tracks, preset, speed and dwell time changeable
Pattern	6 Lines(Pan/Tilt/Zoom, every line can record up to 120 seconds)
Alarm	8 alarm inputs, 2 alarm outputs(optional)
Password protection	YES
Temperature display and Settings	YES(Temperature alarm set, Temperature Display)
Authority Management	YES
Private masking	SONY:24 (Linked Private masking) Samsung: 8 (Linked Private masking)
Address range	0~255 (Setup by dip switcher, firmware)
Communication	RS485 (+/-)
Baud rate	2400/4800/9600/19200
Protocol	PELCO-D, PELCO-P , ULTRACK, VICON, DYNACOLOR
Device title	Display on/off
Zoom times	Display on/off
Firmware Update interface	RS485 (+/-)
Mechanical	
Pan range	0°~ 360° continuously
Pan speed	0.1~ 360°/s
Tilt range	0°~ 90°, Auto Flip 180°to Continue Monitor
Tilt speed	0.1~ 180°/s
Precision	±0.10°
Others	
Housing	Aluminum Alloy, Vandal Proof Housing Wall Mount, Ceiling Mount, Hoop Mount, Corner Mount
Lighting proof	6000V
Ingress protection	IP67
Work temp	-40℃~+60℃
Work humidity	0%~90%
Power	AC24V/2.5A
Weight	4.2KG